

2012 BRUTE FORCE® 750 4X4I EPS CAMO

Kawasaki
Let the good times roll.™



Key Features

- Electric Power Steering (EPS) system results in enhanced handling and improved ride comfort.
- Powerful 749cc 90-degree V-twin engine delivers excellent torque and a distinctive exhaust note
- Engine's digital fuel injection delivers right amount of power throughout the rpm range with fast throttle response
- Independent front and rear suspension provides a comfortable ride and ground following ability
- Limited-slip front differential reduces steering effort under normal four-wheel drive operation, while Variable Front Differential Control permits rider to distribute torque equally to front wheels for maximum traction
- Rider can select two- or four-wheel drive by pressing a button located on the handlebar
- Fitted with pre-routed tubing and mounting brackets for easy winch wiring and installation
- Automotive-style instruments include digital speedometer, odometer, twin trip meters, clock, hour meter and fuel gauge and are mounted for easy viewing
- Dual front disc brakes with two-piston calipers and Kawasaki's sealed, oil-bathed, multi-disc rear brake system provide maximum stopping power
- Trailer hitch bracket with 1,250 pounds of towing capacity is standard equipment
- Waterproof storage box in the left front fender complements the easy-access storage pocket on the right side



Realtree® APG™ HD®

Specifications

Engine	Liquid-cooled, 90-degree, four-stroke V-twin
Valve System	SOHC, four valves per cylinder
Displacement	749cc
Starting System	Electric
Bore X Stroke	85 x 66mm
Compression Ratio	9.3:1
Fuel Injection	DFI®; (2) 36mm Mikuni throttle bodies
Ignition	TCBI with digital advance
Transmission	Continuously variable belt-drive transmission with high and low range, plus reverse, and Kawasaki Engine Brake Control
Final Drive	Selectable four-wheel drive with Variable Front Differential Control, shaft
Frame Type	Double-cradle, high-tensile tubular steel
Front Suspension / Wheel Travel	Double Wishbone/ 6.7 in.
Rear Suspension / Wheel Travel	Fully independent, dual A-arm / 7.5 in.
Front Tire Size	AT25x8-12
Rear Tire Size	AT25x10-12
Front Brakes	Dual hydraulic 200mm discs with 2-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc

Overall Length	86.4 in.
Overall Width	46.5 in.
Overall Height	48.0 in.
Wheelbase	50.6 in.
Turning Radius	10 ft. 6 in.
Ground Clearance	9.4 in.
Seat Height	35.8 in.
Lighting	35W headlights, 5W taillight, 21W stoplight
Rack Capacity, Front / Rear	88 / 176 lbs.
Towing Capacity	1,250 lbs.
Curb Weight	694.6 lbs.
Fuel Capacity	5.0 gal.
Instruments	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS, neutral, reverse, belt, and oil pressure.
Color Choices	Realtree® APG™ HD®
Good Times™ Protection Plan	12, 24, 36 or 48 months
Warranty	12 Months



Main Street Kawasaki

20 S. Main Street

Cape May Court House, NJ 08210

Phone: (609) 465-3900

Email: mainstreetkawie@gmail.com

Website: www.mainstreetkawasaki.com