



2012 MULE™ 610 4X4

Kawasaki
Let the good times roll.™



Dark Royal Red



New Black

Key Features

- Rugged and compact 4x4 off-road utility vehicle can be transported in the back of a full-size pickup truck
- Can tow up to 1,100 pounds with optional Kawasaki trailer hitch installed
- Tilting steel cargo bed helps simplify cleaning and maintenance
- Cargo bed can carry up to 400 pounds
- Fully automatic transmission with selectable two- or four-wheel drive
- Rack-and-pinion steering helps to keep steering light and accurate, which makes maneuvering in tight working quarters a snap
- Unit swingarm rear suspension can handle heavy loads, yet provides a comfortable ride with an empty cargo bed
- Dual-mode differential gives operators options on adverse terrain: one for maximum traction in difficult terrain, the other for decreased turning radius and minimal ground disturbance

Specifications

Engine	Four-stroke, air-cooled single
Displacement	401cc
Bore X Stroke	82 x 76mm
Compression Ratio	8.6:1
Carburetor	Nikki 6C1026
Air Filter	Snorkel-type with two-stage dry replaceable element
Oil Filter	Automotive-type spin-on canister
Ignition	Magneto and transistor
Electrical	12V DC, 14 amp-hour battery, alternator
Transmission	Continuously variable transmission with high and low range, plus reverse
Final Drive	Shaft-driven selectable four-wheel drive, dual-mode rear differential
Exhaust	Muffler with USFS-approved spark arrestor
Front Tire Size	24x9-10 tubeless
Rear Tire Size	24x11-10 tubeless
Front Suspension / Wheel Travel	Independent, MacPherson strut / 3.1 in.
Rear Suspension / Wheel Travel	Unit swing axle / 3.1 in.
Steering	Rack and pinion
Brakes	Four-wheel hydraulic drums, triple sealed
Fuel Capacity	4.1 gal.

Dry Weight	1,010 lbs.
Overall Length	108.8 in.
Overall Width	52.6 in.
Overall Height	70.9 in.
Wheelbase	70.0 in.
Ground Clearance	6.7 in.
Roll Over Protective Structure (ROPS)	This structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5. This structure also meets FMVSS 216 Roof Crush resistance requirement
Cargo Bed Dimensions (Lxwxh)	41.1 x 35.4 x 9.6 in. / 8.08 cu. ft.
Load Capacity	926 lbs.
Cargo Bed Capacity	400 lbs.
Towing Capacity	1,100 lbs.
Turning Radius	10.8 ft.
Top Speed	25 mph, governed
Lighting	(2) 35-watt sealed-beam headlights, (2) 5/21-watt taillight/stoptlight
Instruments	Oil light, hour meter
Color Choices	Dark Royal Red, Woodsman Green
Warranty	12 Months
Good Times™ Protection Plan	12, 24, 36 or 48 months



Main Street Kawasaki

20 S. Main Street

Cape May Court House, NJ 08210

Phone: (609) 465-3900

Email: mainstreetkawie@gmail.com

Website: www.mainstreetkawasaki.com